

Extension 1.5 metres for aluminium column with 4 sides Simon K45

REF. ALK54P15/8



BASIC INFORMATION

DESCRIPTION

Only expand the workplace solutions of their work area with the extension of 1.5 metres for pole 4-sided within the collection Simon K45 made in anodised aluminium for greater resistance and durability of the product, it is advisable to combine one extension per pole to ensure the robustness of the product. With a size of 1500 x 125 x 125 mm, the extension of the K45 range, you can get to reach temperatures in installation of -25°C and most of 120 ° C, exceeding the 120 ° C in construction. For Simon K45, the rank is give your work area the greater workplace solutions, functionality and innovation through designs that adapt perfectly in spaces compact. Once again, Simon K45 offers you the maximum functionality in the minimum space.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

4-sided

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using connecting pins

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050624

PRODUCT NET WEIGHT

7.8

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

24.861

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050624

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

7.8

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

119

PACKAGING NET WEIGHT

7.8

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

139

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

7.8

PACKAGING LENGTH

1503