

Downlight 703.22 Square Comfort WW Wide Flood DALI Black

REF. 70322338-483



BASIC INFORMATION

APPLICATION

Hotel, Restaurants, Residential, Retail, Office, Healthcare, Education

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CUT OFF

No

LUMENS/W

630 lm/7.5 W

IP RATING

IP44

DRIVER INCLUDED

Yes

OPTICS

Wide Flood

OPERATING TEMPERATURE RANGE (°C)

15 - 35 °C

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

LIGHT BEAM APERTURE ANGLE (°)

40°

POWER (W)

7.5 W

COLOR TEMPERATURE (K)

3000 K

COLOR TYPE

WW

SERVICE LIFE

30.000 h

CONTROL

DALI

LIGHTING EFFICIENCY (LM/W)

84 lm/W

CRI

80

LUMENS (LM)

630 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush-mount

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053088777

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.418

PRODUCT NET WEIGHT

0.295

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053088777

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

110

PACKAGING WIDTH

135

PACKAGING LENGTH

170

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2524500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.418

PACKAGING NET WEIGHT

0.295

PACKAGING WEIGHT UNIT

KGM