

## Modular Lighting 729 120X30 Low Glare 4000K

REF. 72951033-684



### BASIC INFORMATION

#### MATERIAL

Aluminium

#### APPLICATION

Office

#### ETIM CLASS

EC002892

### TECHNICAL INFORMATION

#### FREQUENCY

50 - 60 Hz

#### POWER SUPPLY (V~)

220/240 V~

#### COLOR TYPE

NW

#### IP RATING

IP20

#### CONTROL

On/Off

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

50

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021\*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053305119

### UNITARY PACKAGING HEIGHT

35

### UNITARY PACKAGING WIDTH

39

### UNITARY PACKAGING LENGTH

122.2

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

166803

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

2

### PRODUCT NET WEIGHT

1.75

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053305119

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

0

### PACKAGING WIDTH

0

### PACKAGING LENGTH

0

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.75

### PACKAGING WEIGHT UNIT

KGM