30 mA differential with 1 double element trim plate and 42 mm height aluminum Simon Cima

REF. **S195DS/8**



BASIC INFORMATION

FINISH

Aluminium

COMPATIBILITY

With Simon Cima Pro surface and flush-mounted wall boxes, Cima Classic flush-mounted wall boxes with 33mm housing, adjustable floor boxes and reduced depth, and PVC cable guide.

ETIM CLASS

EC000042

TECHNICAL INFORMATION

BREAKING CAPACITY (A)
10000 A (with fuse in front)

CURRENT (A)
30 mA

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

POWER SUPPLY (V~)
125/230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
10

INSTALLATION DIRECTION
Horizontal, Vertical

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436050167

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
753878

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.279

PRODUCT NET WEIGHT
0.279

UNITARY PACKAGING WEIGHT UNIT
KGM

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
118

PACKAGING WIDTH
121

PACKAGING LENGTH
264

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3769392

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
1.395

PACKAGING NET WEIGHT
1.395

PACKAGING WEIGHT UNIT
KGM