

2-way switch 16AX 250V~ with fast terminal connection system white Simon 27 Play

REF. 27211-65



BASIC INFORMATION

DESCRIPTION

It is a 16 AX 250V~ 2-way switch with white finish of the Simon 27 Play series, it is suitable for installation both in surface-mounted and to be recessed and offers a quick terminal connection system that will reduce the times ostensibly. It measures 45x45 mm and it is composed of metal elements with halogen-free thermoplastic insulation and thermoset trim in. These materials guarantees maximum security at all kinds of situation. The piece also has been manufactured in compliance with the regulation. There is the possibility of replacing the finish of the supplied rocker. There are 7 additional finishes available to choose. This reference is compatible with the frames of the series Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. To give you a proper maintenance, it is advisable to clean this 2-way switch with a soft, dry cloth and avoid abrasive products containing chlorine.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 7 additional finishes available.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 AX

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP21

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and
Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE 8421053251881	UNITARY PACKAGING GROSS WEIGHT 0.032	PACKAGING LENGTH 220
UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.032	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 1201200
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8421053035672	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING MEASUREMENT UNIT MMT	UNITS CONTAINED PACKAGING 10	PACKAGING GROSS WEIGHT 0.325
UNITARY PACKAGING VOLUME 1201200	PACKAGING HEIGHT 52	PACKAGING NET WEIGHT 0.32
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING WIDTH 105	PACKAGING WEIGHT UNIT KGM