

PD-24x24 PIR+LUX BT Mesh recessed DALI-2 Input white IP20

REF. 89212316-230



BASIC INFORMATION

DESCRIPTION

Presence and light sensor flush-mounted PIR. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 160°. The tangential detection range is 24 x 24 m and the radial detection range is 9 x 9 m.

The brightness regulation range is 2 - 2000 lux. The detector configuration is done via Bluetooth application and DALI.

It has a TEACH operating mode. Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 19 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: 0 - 40 °C. White finish, protection degree IP 20, and dimensions: 103 x 103 x 67 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342374

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.248

PRODUCT NET WEIGHT

0.14

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342374

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.248

PACKAGING NET WEIGHT

0.14

PACKAGING WEIGHT UNIT

KGM