

Floor trunking distribution baseboard with 2 punched holes (at 180°) and 2 pre-punched holes stainless steel  
**Simon Trunking**

REF. KTA822/8



## BASIC INFORMATION

### DESCRIPTION

Floor trunking distribution baseboard with metallic finish with 2 punched holes (at 180°) and 2 pre-punched holes of stainless steel of the series Simon Trunking. It should be noted that Simon Trunking products are completely adapted to the new trends in the decoration of spaces, maintaining a high degree of aesthetic integration. It is a baseboard which is designed with 4 pre-punched holes for DCS trunking of 85 x 18 mm. The benefit of this product, it is that the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the baseboard using the adapter ALKA02 / 8. An advantage of this product, it is that it can be installed both on a concrete floor and in a raised floor. To be in transit areas, in many cases they may get dirty. For them, the correct way is done only with a soft and dry cloth, because if not could damage the product. And in any way must be attempting to clean the piece with abrasive cloths or cleaners which contain chlorine.

### FINISH

Metal

### PACKAGING CONTENTS

Distribution plinth for floor trunking, protective foam, screws and installation manual

### ETIM CLASS

EC002469

### MATERIAL

Stainless steel

### REMARKS

Designed with 4 pre-punched holes for DCS 85 x 18 mm trunking. See table in the event of requiring a different plinth configuration for the distribution of floor trunking. In addition to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the plinth base, using the adaptor ref. ALKA02/8

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam in the base of the distribution plinth.

### AVAILABLE IN

1 to 3 punched holes 130 x 18 mm and 1 to 4 pre-punched holes 85 x 18 mm (see selection table)

### DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

### EARTHING RESISTANCE

< 0.05 ?

### ELECTRICAL PROPERTIES

With electrical continuity

### HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

### INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

### VERSION

2 punched holes 130 x 18 mm DCS trunking (at 180°) and 2 pre-punched holes 85 x 18 mm DCS trunking

## INSTALLATION AND MAINTENANCE

### TYPE OF FASTENING

Using supplied screws

### INSTALLATION DIRECTION

Horizontal

### INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

### SCREWS REQUIRED FOR FLOOR FIXING

4

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-2:2008

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8426436036598

### PRODUCT NET WEIGHT

0.38

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

1474200

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8426436036598

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

0.38

### UNITARY PACKAGING VOLUME

0.3

### PACKAGING HEIGHT

63

### PACKAGING NET WEIGHT

0.38

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

150

### PACKAGING WEIGHT UNIT

KGM

### UNITARY PACKAGING GROSS WEIGHT

0.38

### PACKAGING LENGTH

156