

Charger 5V DC type A USB port graphite Simon K45

REF. K126B/14



BASIC INFORMATION

DESCRIPTION

So that it does not return to be concerned with stay batteries, the collection Simon K45, offers the 5V / DC charger through type A USB port With a current of up to 1.5 Amps and capable of withstanding 230 Volt voltage, it has a cable section cross-section between 1.0 to 2.5 mm and with two modules, is made up of halogen-free thermoplastic materials, which provide the security necessary in case of fire. With screw terminal connection, the loader of Simon K45, can be inserted in a surface or recessed, adapting to the needs of each room aesthetic and functional. Elegant finishes, effectiveness and security is the Simon K45 solution for that does not have to be concerned carry it its loader.

FINISH

Graphite

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

USB charger, trim cover and installation manual

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

1,5 A

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,0 to 2,5 mm

IP RATING

IP20

NUMBER OF MODULES

2 modules

NUMBER OF CONNECTIONS PER TERMINAL

1 connection per terminal

KIT AVAILABILITY

No

MONOBLOCK

No

MAX TEMP DURING CONSTRUCTION WORK (°C)

0 a 45° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

7021

FORMAT

USB

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 50° C

VERSION

Single

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

6

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE SOCKET

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-038

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

2 inputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2013 + ETSI-EN 301489-34 V1.4.1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.045

PRODUCT NET WEIGHT
0.045

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053134368

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
57

PACKAGING WIDTH
76

PACKAGING LENGTH
76

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
329232

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.045

PACKAGING NET WEIGHT
0.045

PACKAGING WEIGHT UNIT
KGM