

Fastening bracket for Teleblock telescopic profiles with manual elevation Simon K45

REF. KTLA4



BASIC INFORMATION

DESCRIPTION

With black finishes and measures 108x101 mm, the fastening bracket for Teleblock telescopic profiles with manual elevation part of the series Simon K45. This piece is manufactured with thermoplastic materials and self-extinguishing, halogen-free to guarantee no flame spread in case of fire, and low toxicity of smoke. Therefore, this piece is operating normally at temperatures between -5 and 60 ° C, being able to withstand even more than those 60 ° C All this proves to the series Simon K45 has become one of the favourite series for the most demanding customers. And is that our constant effort due to innovate and always offer the best quality and guarantee have allowed our company to consolidate itself as a brand leader in the sector.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Fastening bracket for telescopic profiles with manual elevation and installation manual.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

HEAT RESISTANCE (°C)

+70°C (according to standard IEC
60670)

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

IP RATING

IP4X

KIT AVAILABILITY

No

LINKABLE

No

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

RAL

7021

RECESS DIMENSION (MM)

Ø 114 mm

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+850 °C (according to standard
IEC 60670)

TYPE OF FASTENING

By tightening the fastening
thread supplied with the Simon
K45 Teleblock telescopic profile.
Note: this article is a
replacement part and is supplied
with the Simon K45 Teleblock
telescopic profile.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436051676

PRODUCT NET WEIGHT

0.255

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3217500

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436051676

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.261

UNITARY PACKAGING VOLUME

3217500

PACKAGING HEIGHT

165

PACKAGING NET WEIGHT

0.255

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

130

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.255

PACKAGING LENGTH

150