1 metre extension for aluminium column with 2 sides white Simon 500 Cima

REF. **53555202-030**



BASIC INFORMATION

DESCRIPTION

Once again, the Simon 500 Cima series offers the most effective and efficient solutions for electrical and electronic installations in homes and companies. In this occasion presents the extension of a meter to pole in aluminium finish of the two faces white in colour, a highly demanded by private individuals and professionals in the industry. This is an extension suitable for installing on any floor type, whether raised or concrete. With dimensions of 1000 x 110 x 127 mm, the resistance and duration of this extension is based on the anodised aluminium, a component that predominates in its structure. The fastening of the pole is carried out using a telescopic guide attached to the ceiling slab. Also, Simon remember that to ensure the robustness of the total structure, it is only possible to combine one extension per column.

FINISH

White

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima, Simon 27 Play/Simon K45 (using adaptor) mechanisms and universal Simon mechanisms in combination with the universal box designed specifically for columns.

PACKAGING CONTENTS

Extension and installation manual

ETIM CLASS

EC000795

REMARKS

To ensure the robustness of the total structure, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured with the metal divider guide supplied in the column.

IP RATING

IP4X

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

RAL

9003

VERSION

2 sides

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

TYPE OF FASTENING
Using connecting pins

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Suitable for installing in any floor type, raised or concrete. Column secured by applying pressure to the ceiling slab using a telescopic guide.

REMOVAL OF TRIM FRAMES
Only with tool

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053101902

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
4.705

PRODUCT NET WEIGHT
4.705

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053101902

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
3006

PACKAGING WIDTH
119

PACKAGING LENGTH
139

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.497

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
4.705

PACKAGING WEIGHT UNIT
KGM