

Luminaire HOLE 50 Flush mount 2700K Flood Black CRI98

REF. 91411932-288



BASIC INFORMATION

FINISH

Black

APPLICATION

Flush mount

ETIM CLASS

EC001744

MATERIAL

Aluminium

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LUMENS (LM)

266 lm

IP RATING

IP20

DRIVER INCLUDED

No

LUMENS/W

266

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

33 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

RAL

9005

L90 (°C)

40.000h at 25°C

POWER (W)

3.5 W

COLOR TEMPERATURE (K)

3000 K

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Flush mount

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547055531

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.432

PRODUCT NET WEIGHT

0.432

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8436547055531

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

80

PACKAGING WIDTH

176

PACKAGING LENGTH

290

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4083200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.432

PACKAGING NET WEIGHT

0.432

PACKAGING WEIGHT UNIT

KGM