

## Adjustable depth drawer for 6 S modules to be installed in a false floor color graphite Simon CIMA

REF. SF610/14



### BASIC INFORMATION

#### FINISH

Graphite

#### MATERIAL

Various

#### COMPATIBILITY

With Simon Series S mechanisms and Simon 25 / Simon K45 (via adapter)

#### ETIM CLASS

EC000024

## TECHNICAL INFORMATION

### NUMBER OF CLAMP-HOLDER HOLES

16

### HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

### IK CLASSIFICATION

08

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### MAXIMUM LOAD (KG)

1800kg

### RAL

7021

### RECESS DIMENSION (MM)

210 x 300 mm

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### REMOVAL OF COVER

Only with tool

### REMOVAL OF THE FRAME

Only with tool

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8426436052628

### PRODUCT NET WEIGHT

2.248

### PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING VOLUME

7483280

### UNITARY PACKAGING WIDTH

0

### PACKAGING EAN

8426436052628

### PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING LENGTH

0

### UNITS CONTAINED PACKAGING

1

### PACKAGING GROSS WEIGHT

2.27

### UNITARY PACKAGING VOLUME

0.3

### PACKAGING HEIGHT

98

### PACKAGING NET WEIGHT

2.248

### UNITARY PACKAGING VOLUME UNIT

MMQ

### PACKAGING WIDTH

230

### PACKAGING WEIGHT UNIT

KGM

### UNITARY PACKAGING GROSS WEIGHT

2.248

### PACKAGING LENGTH

332