

PD-8 PIR+LUX recessed DALI-2 Input white IP20

REF. 89212312-130



BASIC INFORMATION

DESCRIPTION

PIR presence and brightness detector for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360°. The tangential detection range is 8 m and the radial detection range is 4.5 m.

The brightness regulation range is 2 - 1000 lux. The detector configuration is done via DALI.

It features a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 12 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

White finish, protection rating IP 20 and dimensions: Ø 109 x 107 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342350

UNITARY PACKAGING GROSS WEIGHT

0.329

PACKAGING LENGTH

140

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.194

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2744000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053342350

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.329

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

140

PACKAGING NET WEIGHT

0.194

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

140

PACKAGING WEIGHT UNIT

KGM