

MD-20 300° PIR+LUX wall surface KNX black IP54

REF. 89202735-438



BASIC INFORMATION

DESCRIPTION

Wall-mounted PIR motion and light detector. The recommended installation height is 2 m, with a maximum height of 5 m. It has a detection angle of 300° and an opening angle of 180°. The tangential detection range is 20 m and the radial detection range is 4 m. The luminosity regulation range is 2 - 1000 lux and the timing range is 1 min - 60 min. The configuration of the detector is carried out through potentiometers and KNX. It features a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 10 mA. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50 °C. Black finish, IP 54 protection rating, and dimensions: 114 x 74 x 128 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Black

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9005

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341711

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.341

PRODUCT NET WEIGHT

0.213

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341711

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

142

PACKAGING LENGTH

100

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2286200

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.341

PACKAGING NET WEIGHT

0.213

PACKAGING WEIGHT UNIT

KGM