Two-pole socket outlet 16A 250V~ for half element with safety device and screw terminal connection white Simon 27 Play

REF. **27431-64**



BASIC INFORMATION

DESCRIPTION

It is a two-pole socket-outlet 16A 250V~ of half an element that includes a device of security. With a white finish, the mechanism offers a system of screw-terminal connection. Remember that a proper terminal connection guarantees the correct functioning of the device is also suitable for replacement or export. This two-pole socket-outlet it is composed of metal parts with halogen-free thermoplastic halogen-free and trim made of thermostable plastic. The quality of these materials allows the mechanism to be installed in any environment, as it is highly resistant to extreme temperatures, measures 22.5x45 mm and does not contain any engraving. It is part of the Simon 27 Play series, a collection that allows you to take the initiative in redecorating spaces. Its mechanisms are equipped with innovative electronic functions adapted to current needs.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

Suitable for replacement or export.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

2,5 mm

NUMBER OF POSSIBLE ELEMENTS

Half element

FORMAT

Two-pole

INDICATOR FUNCTION

No

CURRENT (A)

10 A

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

MONOBLOCK

No

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American, Small spaces and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252062

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.033

PRODUCT NET WEIGHT
0.033

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053038086

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
52

PACKAGING WIDTH
105

PACKAGING LENGTH
220

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1201200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.665

PACKAGING NET WEIGHT
0.66

PACKAGING WEIGHT UNIT
KGM