

## Downlight 725.23 Flush mount WW General 1-10V White

REF. 72523130-983



### BASIC INFORMATION

#### DESCRIPTION

Downlight 725.23 Advance, with light colour LED drop (WW) must be installed flush-mounted and the electric control is performed by 1-10 V has a temperature of the colour of 3100 K and 1200 lumens to 14 W power. This product of indoor lighting, it belongs to the series Simon 725 and has a beautiful and simple finish is white in colour. The optics from the Downlight is GENERAL. It is a Downlight category A. its power supply is 100-240 V and its frequency is 50 / 60 Hz, with dimensions of 165 x 51 millimetres and a weight of the luminaire, 0.5 kilos, it is a product compact, which lawyer by the best capacity of light distribution. This Downlight of Simon withstands very variable temperatures, which can oscillate between -15 degrees centigrade and the + 40 degrees centigrade. Thanks to the innovation of the that aims Simon in the manufacture of its luminaires, the Downlight has a very high durability.

#### APPLICATION

General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY (HZ)

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS (LM)

1200 lm

### IP RATING

IP20

### ELECTRICAL CLASS

Type 1

### LUMENS/W

1200 lm/14W

### OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

### INTEGRATED POWER SUPPLY

Yes

### OPTICS

General

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

3100 K

### LIGHT BEAM APERTURE ANGLE (°)

120°

### POWER (W)

14 W

### CONTROL

1-10 V

### COLOR TYPE

WW

### SERVICE LIFE

30.000 h


### CRI

80

### LIGHTING EFFICIENCY (LM/W)

86 lm/W

### CHROMATICS CRI ICONS



## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Surface

### INSTALLATION TYPE

Flush mount

### MINIMUM INSTALLATION HEIGHT

101

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053116845	2.888
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	80	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.528	190	0.528
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.528	190	KGM