

USB 2.0 connector type A female with trim plate white Simon K45

REF. K128B/9



BASIC INFORMATION

DESCRIPTION

The Brand Simon, it works continuously to obtain the best results with their products. In both the safety of people, and the equipment. To do this, use self-extinguishing fireproof materials, and radius of curvature in its boxes and elements that use cables to ensure the non existence of electromagnetic waves that cause undesired interference. This is a USB connector (universal serial bus). The brand Simon works with the best materials in a bus standard which defines the cables, connectors and protocols used to connect, communicating and electrical power supply of between computers, peripheral devices and all kinds of electronic devices. Female type A USB 2.0 connector with white trim plate. Finish Simon K45. screw terminal connection installation by Insertion. Maximum recommended length of cabling: 5 metres for low-speed devices (keyboards, mice) and 2.2 metres for high-speed devices (printers, hard drives,). For more information, please refer to the product instruction sheet. Plate Individual 1 / 2 element, 1 module. Suitable for surface mounting and flush mounting. Cabling from 0.2 to 0.5 mm, withstands temperatures from 5 to 40° C and of -25 to 50° C. Metal components with thermoplastic insulation auto-extinguishing and halogen-free; guarantees no flame propagation in case of fire and low toxicity in case of smoke dimensions 22.5x45 mm Easy cleaning and maintenance, it is recommended not to use abrasive cleaners containing chlorine.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female type A USB 2.0 connector, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 5 metres for low-speed devices (keyboards, mice) and 2.2 metres for high-speed devices (printers, hard drives, etc.) For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 0,2 to 0,5 mm

REVISION

+34 2.0

CONNECTOR TYPE

USB

NUMBER OF CONTACTS

5

NUMBER OF POSSIBLE ELEMENTS

1/2 element

FORMAT

USB

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

RAL

9003

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

NUMBER OF WIRES

5

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436064799

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436064799

PACKAGING VOLUME

0.012

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.023

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

42

PACKAGING NET WEIGHT

0.02

UNITARY PACKAGING GROSS
WEIGHT

0.02

PACKAGING LENGTH

50

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.02