

Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 6 FTP black Simon K45

REF. KB96F/14



BASIC INFORMATION

DESCRIPTION

With the elegance of avant-garde finishes in black, the plate of voice and data flat plate with dust cover with 1 element and 2 RJ45 category 6 FTP connectors,, in the collection Simon K45, it provides to their stay high speed data transmission, with a simple installation that facilitates cable management. With category 5e UTP and compatible with Keystone-type ports, the flat base plate Simon K45, maximize the functionalities of the product, at the same time that promotes the integration of the set in any type of space. Its installation, suitable for surface-mounted or recessed, is direct snap-fit without screws and, for an extra versatility, you can prepare in vertical enclosures thanks to 90 ° positioner (ref.K66) for an optimal orientation of the product. Manufactured in thermoplastic autoextinguible halogen-free, prevents the flame spread. Security, functionality and innovation in the Simon K45 range.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Voice and data flat plate with dust cover, RJ45 category 6 FTP connectors and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90° positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-24 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

With insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Supplied with voice and data plate

CONNECTOR CHARACTERISTICS

Category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

MAX TEMP DURING

CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

Single

NUMBER OF MODULES

Half

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

INSTALLATION TYPE

Suitable for surface and flush mounting

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.056

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

3524976

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8426436047907

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

3891888

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.56

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

112

PACKAGING NET WEIGHT

0.56

UNITARY PACKAGING GROSS WEIGHT

0.056

PACKAGING WIDTH

117

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

269