

IP66 mechanism holder unit with safety lock and a schuko socket with 1RJ45 category 6 UTP stainless steel Simon K45

REF. KSE16USEC/23/72



BASIC INFORMATION

DESCRIPTION

With the range update, its equivalent for the new version is the KFH116USEC/72 reference.

FINISH

Stainless steel

MATERIAL

Stainless steel

ETIM CLASS

EC000024

TECHNICAL INFORMATION

DUST SHUTTER

No

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1000kg

FORMAT

Schuko

IP RATING

IP66

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

KIT AVAILABILITY

No

VOLTAGE (V~)

250 V~

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053297810

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.354

PRODUCT NET WEIGHT

0.354

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053297810

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

160

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1664000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.404

PACKAGING NET WEIGHT

0.354

PACKAGING WEIGHT UNIT

KGM