

IP66 mechanism holder unit with safety lock and a French socket base with 1RJ45 category 5e UTP stainless steel Simon K45

REF. KSE25USEC/23/72



BASIC INFORMATION

DESCRIPTION

With the range update, its equivalent for the new version is the KFH125USEC/72 reference.

FINISH

Stainless steel

MATERIAL

Stainless steel

ETIM CLASS

EC000024

TECHNICAL INFORMATION

DUST SHUTTER

No

FORMAT

French

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INDICATOR FUNCTION

No

CURRENT (A)

16 A

IP RATING

IP66

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)

1000kg

RECESS DIMENSION (MM)

145 x 145 mm en falso suelo

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

NUMBER OF COVER OPENING POSITIONS

1

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

CAN BE INSTALLED IN TRAY

Plástica

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436063884

PRODUCT NET WEIGHT

0.46

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1.445

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436063884

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.46

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

77

PACKAGING NET WEIGHT

0.46

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

137

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.46

PACKAGING LENGTH

137