Push-button switch with bell symbol 10A 250V~, built-in light and fast terminal connection system ivory Simon 31

REF. **31660-31**



BASIC INFORMATION

DESCRIPTION

Push-button switch with bell engraving, 10 A current and 250V, built in LED system and quick terminal connection, in ivory colour and belonging to the series Simon 31. It works by tilting and can be combined with the reference 31802.31 in case of replacement of the indicator light and, in addition, it has 2 modules and supports a wire cross section of 1.5 to 2.5 mm, with a stripping of 11 mm, approximately. In addition, it can be installed on surfaces with a temperature located between 5 and 40ºC, approximately, although it can withstand extreme temperatures of -25 to 50ºC, approximately. Its dimensions are 64x65mm and complies with the European standards and regulations UNE -s 60669-1: 2002 + A1: 2003 + A2: 2009 standards, in addition to being manufactured with metal components with halogen-free insulation and thermoplastic trim. To clean it, it will only need to use a soft and dry cloth, slightly dampened in soapy water and never use abrasive cloths or cleaners that contain chlorine in its formula.

FINISH
Ivory

COMPATIBILITY
Simon 31 frames

ETIM CLASS
EC000029

MATERIAL
Thermoplastic

PACKAGING CONTENTS
Mechanism with rocker

REMARKS
Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

INDICATOR FUNCTION
Yes

TYPE OF MECHANISM
Pivoting

CABLE SECTION ADMITTED (MM)
From 1,5 to 2,5 mm

IP RATING
IP20

NOMINAL VOLTAGE (V~)
250 V~

CONSUMPTION INDICATOR (MA)
1 mA

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (ºC)
5 - 40 ºC

NUMBER OF POSSIBLE ELEMENTS
1 element

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

INSTALLATION TYPE
Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.091

PRODUCT NET WEIGHT
0.091

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053007402

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
83

PACKAGING WIDTH
165

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3026595

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.91

PACKAGING NET WEIGHT
0.91

PACKAGING WEIGHT UNIT
KGM