

Flat voice and data plate with dust cover for 2 RJ45 BeldenCDT® for 1 element aluminium Simon 500 Cima

REF. 50013089-033



BASIC INFORMATION

DESCRIPTION

With an innovative design that will allow you to change the image of a stay in a few minutes without any previous knowledge to perform installation, the Simon 500 Cima series has included in its wide catalog of products and accessories for electrical and electronic systems is the flat plate for voice and data with dust cover for two BeldenCDT RJ45 connectors for one element in aluminium finish. The halogen-free thermoplastic is the component is present in its structure, a component that guarantees no flame propagation in case of fire and the low toxicity in case of smoke. That is why we are between one of the most reliable of Simon, in addition to one of the most competitive thanks to its low price. Also, the plate includes clips for fastening in vertical and horizontal enclosures without the need for an adaptor.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

COMPATIBLE WITH CONNECTORS

BeldenCDT® GigaFlex MDVO.

RJ45 CONNECTORS

Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST PROTECTION

Yes

FORMAT

RJ45

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

1

PLATE TYPE

Flat

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

BeldenCDT® RJ45 connectors

SNAP-FIT TYPE

BeldenCDT® RJ45 connectors

VERSION

Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053096765

PACKAGING VOLUME
0.604

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
54

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.018

PACKAGING WIDTH
52

PACKAGING NET WEIGHT
0.18

PRODUCT NET WEIGHT
0.018

PACKAGING LENGTH
215

PACKAGING WEIGHT UNIT
KGM

