

Projector 889 300W 3000K

REF. 88936038-883



BASIC INFORMATION

DESCRIPTION

Outdoor LED projector for illuminating shop windows and facades, robust, tiltable, and designed for high performance in commercial applications. Available in different power ratings, the outdoor projector 889 allows selecting the appropriate model based on mounting height, the surface to be illuminated, and the desired level of impact. Installation type: Surface. Optics: 110. Color temperature: 3000K. Power: 300W. Lumens: 27000lm. Efficiency: 90lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 498 mm x 412 mm x 48 mm.

APPLICATION

Wall lighting, Industrial
lighting, Commercial areas

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

05

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+50

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

90 lm/W

LUMENS (LM)

27000 lm

OPTICS

Symmetric

POWER (W)

300 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440346

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

4.432

PRODUCT NET WEIGHT

4.28

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440346

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

435

PACKAGING WIDTH

130

PACKAGING LENGTH

525

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

29688750

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

8.864

PACKAGING NET WEIGHT

4.28

PACKAGING WEIGHT UNIT

KGM