

French socket outlet 16A 250V with safety device and quick terminal connection orange Simon K45

REF. K22/7



BASIC INFORMATION

DESCRIPTION

In this category of sockets and covers for electrical outlets, you will find socket outlets of all types and for all kinds of needs. The series Simon K45, for example, deals with everything related to the workplace solutions in the different work stations. To this same collection belongs this French socket outlet (16 Ampere current and 250 Volt voltage), with safety device and type of quick terminal connection. Only for the most daring, as its finish is in orange colour. In terms of the wire section admitted is from 1.5 to 2.5 mm (stripping of wire to 12 millimetres). However, it is possible to link socket outlets directly, without the need for stripping or braiding different wires, with article No. AC11. Like every product of the Simon brand, it is made of high quality components: Metal components, in this case, which have self-extinguishing, halogen-free thermoplastic insulation; guaranteeing no flame propagation in case of fire and low toxicity in the event of smoke.

FINISH

Orange

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-03X)

PACKAGING CONTENTS

Socket plug with trim cover and installation manual

ETIM CLASS

EC000125

REMARKS

Ability to link socket plugs directly without stripping or twisting cables, with article No. AC11

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

NUMBER OF MODULES

2 modules

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

CURRENT (A)

16 A

MONOBLOCK

No

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

LINKABLE

Yes, using accessory AC11

RAL

2009

FORMAT

French

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

NUMBER OF SOCKETS

1

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Insertion

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45
and specific Simon 500 Cima
using adaptor ref.50012088-03X

REMOVAL OF THE SOCKET

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in
accordance with standard IEC
60695-10-2)

INSTALLATION DIRECTION

Vertical according to the
direction of the mechanisms

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

INSTALLATION TYPE

Suitable for surface and flush
mounting

NUMBER OF TERMINALS

2 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.061

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

1212505

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053123263

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0.3

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.53

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

49

PACKAGING NET WEIGHT

0.61

UNITARY PACKAGING GROSS

WEIGHT

0.061

PACKAGING WIDTH

101

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

245