

Downlight 725.23 Flush mount NW General Aluminium

REF. 72523033-984



BASIC INFORMATION

DESCRIPTION

The line Downlight 725.23 of the Company Simon, brings together all the conditions needed to achieve a brightness of 100% when switched on. This is due to Simon's extensive experience in the LEDs, which uses all its resources of research to be at the height of the highest quality in the market. This results in the long service life of the luminaire and the resulting saving in maintenance costs due to the fact that the LEDs are not changed often. This also guarantees minimal glare and high visual comfort. Its continuous flicker-free light avoiding visual fatigue and is suitable for places such as hotels, offices, hospitals, etc. This is the luminaire indoor lighting Downlight 725.23 flush-mounted. Colour temperature 3900 K NW Advance. General lighting. The light beam is sent to the bottom with an angle of 40°, which makes the vision of work areas. Category A 30,000 h at 25 ° C. 100-240 V 50 / 60 Hz. ON-OFF switching system with adjustment options of 1-10 V Weight 0.5 kg Material Aluminium. For flush mounting using an accessory. Dimensions 165x51 mm

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY (HZ)

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

IP RATING

IP20

ELECTRICAL CLASS

Type 1

LUMENS/W

1300 lm/14W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

14 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h


CRI

80

LIGHTING EFFICIENCY (LM/W)

93 lm/W

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

101

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING MEASUREMENT UNIT
0	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053116814	3.042
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	80	0
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.504	195	0.504
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.504	195	KGM