

# MD-30x4 High Ceiling Hallways PIR+LUX surface DALI-2 Input white IP54

REF. 89206337-230



## BASIC INFORMATION

### DESCRIPTION

PIR surface motion and light detector. The recommended installation height is 12 m, with a maximum height of 16 m. It has a detection angle of 360° and a opening angle of 90°. The tangential detection range is 30 x 4 m and the radial detection range is 30 x 4 m.

The light regulation range is 2 - 1000 lux. The configuration of the detector is done via DALI.

Possibility of interconnection between sensors through DALI. The control protocol is DALI-2 Input. The typical consumption is 5 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 54 protection grade and dimensions: 95 x 95 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

### FINISH

White

### COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

### ETIM CLASS

EC001582

## TECHNICAL INFORMATION

### IP RATING

IP54

### RAL

9003

### POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

### CONTROL

DALI2 Slave

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

4

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053342053

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.242

### PRODUCT NET WEIGHT

0.152

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053342053

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

124

### PACKAGING LENGTH

160

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1785600

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.242

### PACKAGING NET WEIGHT

0.152

### PACKAGING WEIGHT UNIT

KGM