

Front kit for 2 elements with 1 German socket outlet, 1 rocker and 1 USB charger gloss black Simon 100

REF. 10020207-138



BASIC INFORMATION

DESCRIPTION

This type of front kit can accommodate 2 elements and comes with 1 Schuko plug base, 1 key and 1 black USB charger in a glossy finish. It is a device that is included in the Simon 100 series and therefore, it is compatible with the rest of the signature devices. Simon recommends that it be used in bedrooms and stands out for offering USB connector, plug and light switch that can be by push-button switch.

The intensity of the Schuko is 16A, of the crossing 10 AX and USB 2.1 A, with 250 V ~. It has a type of emborning by cutting (1 click) and USB screw. Its operation is based both by a push-button and by insertion.

This kit stands out for being easy and comfortable, allowing installation vertically and horizontally. The material with which it is designed makes it resistant and capable of being functional between 5 and 40°C, and can even hold up to a maximum of -25 and 50°C in terms of storage temperature.

The device follows the regulations: directive 2014/35 / UE LVD + directive 2014/30 / UE EMC + directive 2011/65 / UE RoHS + EN 50581: 2012 + EN 60669-1: 1999 + EN 60669-1: 1999 A1: 2002 + EN 60669-1: 1999 A2: 2008 * 2 + EN 60950-1: 2006 + EN 60950-1: 2006 A11: 2009 + EN 60950-1: 2006 A1: 2010 + EN 60950-1: 2006 A12: 2011 + EN 60950-1: 2006 A2: 2011 * 3.

FINISH

Gloss black

COMPATIBILITY

Kit mechanisms Simon 100

ETIM CLASS

EC000007

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Cover and rockers

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

2 elements

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

FORMAT

Schuko,USB

MONOBLOCK

Yes

VERSION

2 elements

INDICATOR FUNCTION

No

INSTALLATION AND MAINTENANCE

INSTALLATION DIRECTION

Vertical and horizontal

INSTALLATION TYPE

Suitable for recess

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2: 2008*2 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053192085

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053192085

PACKAGING VOLUME

329406

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0.096

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

155

PACKAGING NET WEIGHT

0.096

UNITARY PACKAGING GROSS
WEIGHT

0.096

PACKAGING LENGTH

84

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.096