Hinged cover for adjustable floor box or service cover in concrete or raised floor for 12 elements grey Simon 500 Cima

REF. **RSF006/1**



BASIC INFORMATION

DESCRIPTION

This product is perfect for adjustable floor boxes or inspection covers embedded in concrete or raised floor. Depth, with capacity to supply power to 12 elements; and is part of the Simon 500 Cima series. It is a hinged lid, complement perfect for this type of installations. There is not to mention the adjustable floor boxes include of Simon since its hinged lids, but the company also offers these parts of an individual so that they can be used as a spare in the event of breakage or loss of the original. The dimensions of the cover are 200 x 292 millimetres and 15 millimetres and its innovative and stylish grey colour, it will make it perfect in any room of the home, premises or office is placed. The cover is manufactured with metal components with self-extinguishing thermoplastic insulation and halogen free, so that it is a product of great quality and security, because they do not contributes to propagate the flame in case of fire.

FINISH

Grey

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam

AVAILABLE IN
2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+90 °C

HEAT RESISTANCE (°C)
+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
>5 MOhms at 500V

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60 °C

NUMBER OF MODULES
12 modules

RAL
7011

VERSION
12 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING
Via coupling pin supplied on the cover

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS
UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436056268

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
1.325

PRODUCT NET WEIGHT
1.325

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436056268

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
20

PACKAGING WIDTH
350

PACKAGING LENGTH
250

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1.75

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.325

PACKAGING WEIGHT UNIT
KGM