

MD-30x4 High Ceiling Hallways PIR+LUX surface KNX white IP54

REF. 89206737-230



BASIC INFORMATION

DESCRIPTION

Surface PIR motion and brightness detector. The recommended installation height is 12 m, with a maximum height of 16 m. It has a detection angle of 360° and an opening angle of 90°. The tangential detection range is 30 x 4 m and the radial detection range is 30 x 4 m. The brightness regulation range is 2 - 1000 lux and the timing range is 1 min - 255 min. The detector configuration is performed via potentiometers and KNX. It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 12.5 mA. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: -20 - 50°C. White finish, IP 54 protection rating, and dimensions: 95 x 95 x 65 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH
White

**COMPATIBLE WITH MECHANICAL
PUSH BUTTON**
No

ETIM CLASS
EC001582

TECHNICAL INFORMATION

IP RATING

IP54

RAL

9003

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

4

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342077

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.246

PRODUCT NET WEIGHT

0.156

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342077

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

124

PACKAGING LENGTH

160

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1785600

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.246

PACKAGING NET WEIGHT

0.156

PACKAGING WEIGHT UNIT

KGM