


Front face kit for 2 elements with 1 2xUSB charger and 1 2P socket outlet gloss white Simon 100

REF. 10020223-130



BASIC INFORMATION

FINISH

Gloss white

ETIM CLASS

EC000007

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

TYPE OF MECHANISM

Insertion

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Suitable for flush mounting

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

2P socket: Connection (1 click®)

TYPE OF TERMINAL

CONNECTION - FUNCTION 2

USB: Screw

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011*3 + ETSI-EN 301489-34 v14.1*3 + IEC 60884-1 Ed. 3.2*1

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053232118

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053232118

PACKAGING VOLUME

329.406

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

CMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

25.3

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

0.081

UNITARY PACKAGING GROSS WEIGHT

0.081

PACKAGING LENGTH

155

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.081