Floor trunking distributor baseboard with 1 punched hole and 3 pre-punched holes for DCS trunking stainless steel Simon Trunking

REF. **KTA813/8**



BASIC INFORMATION

DESCRIPTION

Floor trunking distribution baseboards with 1 and 3 punched hole pre-punched holes for DCS trunking stainless steel of the series Simon Trunking, built with dimensions which are 140 x 140 x 30 mm, it also has a metallic finish, which allow you to make your floors shine, and that the channels help to achieve a modern and modern decoration. If you want to keep it clean and with a perfect and unbeatable, you just need a soft, dry cloth, do not recurras or cloths or abrasive cleaners containing chlorine, as they could damage the piece to be fully stainless steel. This baseboard, it is suitable for installation on any floor type, whether raised or concrete. It is to be able to accomplish this, this product of the series Simon Trunking, it is designed with 4 pre-punched holes for DCS trunking of 85 x 18 mm, it also to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the baseboard using the adapter ALKA02 / 8.

FINISH

Metal

MATERIAL

Stainless steel

PACKAGING CONTENTS

Distribution plinth for floor trunking, protective foam, screws and installation manual

ETIM CLASS

EC002469

REMARKS

Designed with 4 pre-punched holes for DCS 85 x 18 mm trunking. See table in the event of requiring a different plinth configuration for the distribution of floor trunking. In addition to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the plinth base, using the adaptor ref. ALKA02/8

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the inclusion of protective foam in the base of the distribution plinth.

AVAILABLE IN
1 to 3 punched holes 130 x 18 mm and 1 to 4 pre-punched holes 85 x 18 mm (see selection table)

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+120° C

EARTHING RESISTANCE
< 0.05 ?

ELECTRICAL PROPERTIES
With electrical continuity

HEAT RESISTANCE (°C)
+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)
5 MOhms at 500 V.

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

VERSION
1 punched hole 130x18 mm DCS and 3 pre-punched holes 85x18 mm DCS trunking

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING
Using supplied screws

INSTALLATION DIRECTION
Horizontal

INSTALLATION TYPE
Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING
4

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436036581

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1474200

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.395

PRODUCT NET WEIGHT
0.395

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436036581

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
63

PACKAGING WIDTH
150

PACKAGING LENGTH
156

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1474200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.391

PACKAGING NET WEIGHT
0.395

PACKAGING WEIGHT UNIT
KGM