

Switch for blinds 10A 250V~ for half element with 3 positions: up, down and stop ivory Simon 27 Play

REF. 27333-61



BASIC INFORMATION

DESCRIPTION

Do you already know the revolutionary range of the Simon 27 Play series? Why revolutionary? As because it allows you to change the look of your electrical mechanisms to jog the rocker or cover with a single click. Ideal for all those people who like to adapt the style of your home to different environments and as a function of the required for each occasion. For this type of mechanisms, we need to have different parts. One of them can be a switch for blinds, such as this one. This switch for blinds 10A 250V ~, half element, with 3 positions: Raise, lower and stop. Wonderful ivory finish that can be modified by the different finishes offered by the Simon 27 Play series to configure the design of its mechanisms in any moment. It includes engraving indicating the raising, lowering and stopping of blinds. The best manufacturing material, this switch for blinds, has been made with a socket of metal components with halogen-free insulation and thermoplastic trim.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000044

REMARKS

Mechanism with centre position to stop the up/down movement of the blinds.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 A

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

Half element

LATCH TYPE

Mechanical

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

CLAW

Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American, Small
spaces and Centralisations

INSTALLATION TYPE

Suitable for surface and flush
mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053251980

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.027

PRODUCT NET WEIGHT

0.027

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053080801

UNITS CONTAINED PACKAGING

5

PACKAGING HEIGHT

54

PACKAGING WIDTH

52

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

365040

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.135

PACKAGING NET WEIGHT

0.135

PACKAGING WEIGHT UNIT

KGM