Floor trunking 2m and 130x18mm with 3 compartments

REF. **TF11183/8**



BASIC INFORMATION

DESCRIPTION

The DCS TF11183/8 floor trunking with anodized aluminum cover is ideal for the distribution of electrical and data cabling indoors, especially in demanding environments. With a 130x18 mm profile, it stands out for its IK07 protection rating, ensuring resistance to impacts and frequent use. It supports a maximum load of 55 kg/cm^2, making it suitable for offices, commercial spaces, and educational environments. Its installation is simple and fast, thanks to predefined fixing points, allowing easy access for maintenance through the removal of the cover with specific tools.

FINISH	MATERIAL	ETIM CLASS
Aluminium	Aluminium	EC000722

TECHNICAL INFORMATION

IK CLASSIFICATION
07

KIT AVAILABILITY
No

RAL
7035

IP RATING
IP4X

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
Only with tool

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053229095

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
1.375

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436027923

UNITS CONTAINED PACKAGING
8

PACKAGING HEIGHT
90

PACKAGING WIDTH
145

PACKAGING LENGTH
2005

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
26165250

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
11

PACKAGING NET WEIGHT
11

PACKAGING WEIGHT UNIT
KGM