

Modular Luminaire 720 Advance M2 120x30 WW 1-10V

REF. 72061120-883



BASIC INFORMATION

DESCRIPTION

Luminaire Modular Advance M2 of the series 720. It has category B Ecorrae and a translucent optics type. Its colour temperature is 3000 K and its light intensity of 2200 lm / 18 W, while its frequency is 50 / 60 Hz. It is fed through a power 100-240 V and its control is carried out by means of On / Off. It works perfectly in places with a maximum temperature of 40°C (which makes it perfect for any type of climatology), and by working at 25 ° C, offering a service life of a 40,000 hours, approximately. It is a type of luminaire with perfect for false ceiling, visible hardware and its finished in white colour makes it a luminaire ideal for any type of style and decoration. It measures 1195 x 295 x 60 mm and has a weight of 4,9 kg, it also, we can highlight of the luminaire 720 of the series that presents a maintenance simple because you will not have to recámara lamps not clean the luminaire.

DIFFUSER MATERIAL

PMMA

PACKAGING CONTENTS

1 unit

APPLICATION

General lighting

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LIGHTING EFFICIENCY (LM/W)

122 lm/W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

LUMENS (LM)

2200 lm

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

Yes

LUMENS/W

2200 lm/18W

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

100,000 h at 25 °C

OPTICS

Translucent

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

40,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

18 W

CRI

82


COLOR TYPE

WW

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Plaster ceiling, surface mount, concealed or semi-concealed profile.

MINIMUM INSTALLATION HEIGHT

120

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

INSTALLATION TYPE

False ceiling, visible hardware

REGULATIONS

WARRANTY

5 years 50,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.56

PRODUCT NET WEIGHT

5

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053124802

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

65

PACKAGING WIDTH

300

PACKAGING LENGTH

1200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.234

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

5.56

PACKAGING NET WEIGHT

5

PACKAGING WEIGHT UNIT

KGM