

IP66 Mechanism holder and manual frame with 2 french socket and 2 RJ45 Keystone lodge

REF. KFH221/72



BASIC INFORMATION

DESCRIPTION

Simon completely renews its range of waterproof floor boxes for indoor and outdoor environments. This is a manual closure frame for mechanisms with 2 French sockets and accommodation for 2 RJ45 Keystone connectors. In combination with its housing, it allows for installation in technical flooring or pavement. The product design, along with its manufacturing in stainless steel, achieves a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm² from any direction, reaching an IP66 protection rating when the cover is closed. It also supports a maximum load of 2000 kg and has an IK08 impact resistance. It maintains an optimal cable bend radius for high-category voice and data connections. Our accessory for plug connection with a closed cover is available, allowing us to keep our connections active with an IP54 rating (see reference KFA1001), the possibility of leveling our box in case of irregular flooring (see reference KFA1003), or the ability to concatenate more than one box (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

French

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

2000 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

REMOVAL OF THE SOCKET

Only with tool

NUMBER OF COVER OPENING POSITIONS

1

REMOVAL OF THE FRAME

Only with tool

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60670-23:2008 | EN IEC 63000:2018 | IEC 60884-1 Ed 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053334997

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.775

PRODUCT NET WEIGHT

0.682

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053334997

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

114

PACKAGING WIDTH

125

PACKAGING LENGTH

180

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2565000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.775

PACKAGING NET WEIGHT

0.682

PACKAGING WEIGHT UNIT

KGM