

RCCB 30 mA for 2 elements with trim plate white Simon 500 Cima

REF. 50002075-030



BASIC INFORMATION

DESCRIPTION

One of the mechanisms and base plates for circuit protection more prominent of the series is the Simon 500 Cima differential 30 mA 2 elements with trim plate in white colour, with dimensions of 100x50x76 mm, supports a section of wire up to 25 mm and stripping of wire 10 mm at the best price and with the best features. Suitable for flush mount wall installation and recess and clipping in any enclosure of the range except for the floor boxes, this mechanism offers the possibility of request, in case of breakage, cover spare DIN rail adaptor part available at reference 50000076-039. The hardness and resistance to the passage of time and temperature ranges high must be to the metal components with self-extinguishing and halogen-free thermoplastic insulation.; guarantees no flame propagation in case of fire and low toxicity in the event of smoke generation.

FINISH

White

PACKAGING CONTENTS

Differential switch 30 mA, trim plate, adaptor for enclosure Simon 500 Cima (not suitable for installing in floor box) and installation manual

ETIM CLASS

EC000042

COMPATIBILITY

Wall boxes, mini towers, mini columns, columns and metal enclosures Simon 500 Cima

REMARKS

Possibility to order replacement DIN rail adaptor in case of breakage, with article no.50000076-039

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
Up to 25 mm

AVAILABLE IN
Two-pole circuit breaker 10A

BREAKING CAPACITY (A)
10000 A (with fuse in front)

CLASS
AC

NUMBER OF CONNECTIONS PER
TERMINAL
1 connection per terminal

MAX TEMP DURING
CONSTRUCTION WORK (°C)
+60 °C

FORMAT
DIN

INDICATOR FUNCTION
No

CURRENT (A)
30 mA

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING
INSTALLATION (°C)
-5 to 60 °C

TYPE OF MECHANISM
Pivoting

NUMBER OF MODULES
2

POWER SUPPLY (V~)
125/230 V~

RAL
9003

TYPE
Differential switch

VERSION
Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY
(MM)
10

INSTALLABLE IN FLUSH MOUNT
JUNCTION BOX
Specific Simon 500 Cima

INSTALLATION DIRECTION
Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE
Suitable for flush or surface-mount wall installations and snap-fit in any enclosure in the range except for the floor boxes

REMOVAL OF THE MCB
Only with tool

TYPE OF TERMINAL
CONNECTION - FUNCTION 1
Screw

NUMBER OF TERMINALS
4 (2 terminal connectors per pole)

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 61008-1:2012 + EN 61008-1:2012 A1:2014 + EN 61008-1:2012 A2:2014 + EN 61008-1:2012 A11:2015 + EN 61008-2-1:1994 + EN 61008-2-1:1994 A11:1998 + EN 61543:1995 + EN 61543:1995 A112003 + EN 61543:1995 A12:2005 + EN 61543:1995 A2:2006

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053095928

PACKAGING VOLUME

3524976

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

5

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

112

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.234

PACKAGING WIDTH

117

PACKAGING NET WEIGHT

1.17

PRODUCT NET WEIGHT

0.234

PACKAGING LENGTH

269

PACKAGING WEIGHT UNIT

KGM

