

**PD-12 HF+LUX BT Mesh recessed box DALI-2 Input white
IP20**

REF. 89214323-230



BASIC INFORMATION

DESCRIPTION

Presence and luminosity detector for flush mounting HF. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 140°. The tangential detection range is 12 m and the radial detection range is 12 m.

The luminosity regulation range is 2 - 2000 lux. The detector configuration is done via a Bluetooth application.

Possibility of interconnection between sensors via Bluetooth and DALI. The control protocol is DALI-2 Input. The typical consumption is 21 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C.

White finish, protection degree IP 20 and dimensions: 103 x 103 x 61 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342558

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.251

PRODUCT NET WEIGHT

0.143

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342558

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

161

PACKAGING WIDTH

101

PACKAGING LENGTH

143

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2325323

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.251

PACKAGING NET WEIGHT

0.143

PACKAGING WEIGHT UNIT

KGM