Plastic tray for square shallow floor box in concrete floor for 8 elements Simon 500 Cima

REF. **G401**



BASIC INFORMATION

DESCRIPTION

La serie Simon 500 Cima tiene incluida en su amplio catálogo la Cubeta de plástico para caja de suelo cuadrada de profundidad reducida en pavimento para ocho elementos. Con unas dimensiones de 419 x 384 x 54 mm, el revestimiento del suelo debe colocarse hasta la entrada de la tapa protectora a la hora de realizar su instalación, que puede llevarse a cabo sin necesidad de conocimientos previos profesionales en unos minutos. Así de fácil y sencillo. Especialmente diseñada para ser instalada en suelos de pavimento, centros educativos, hospitales u hoteles ya disfrutan de todas las ventajas de esta cubeta. Resistencia, durabilidad y seguridad son tres características presentes en su estructura fabricada con material termoplástico libre de halógenos, componente que garantiza la no propagación de llama en caso de incendio y la baja toxicidad en caso de emisión de humos.

FINISH

Green

MATERIAL

Plastic

COMPATIBILITY

Reduced depth floor boxes Simon CIMA / K45

PACKAGING CONTENTS

Tray and protective cover with installation manual

ETIM CLASS

EC000114

REMARKS

The floor lining must be installed up to the protective cover inlet

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

4, 6 and 8 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (ºC)

+90 ºC

HEAT RESISTANCE (ºC)

+125ºC (according rule IEC 60695-10-2)

IK CLASSIFICATION

08

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

IP RATING

IP4X

KIT AVAILABILITY

No

TEMPERATURE RANGE DURING INSTALLATION (ºC)

-5 to 60 ºC

NUMBER OF MODULES

8 modules

RECESS DIMENSION (MM)

419 x 384 mm

NUMBER OF SIDE ENTRANCES

8

VERSION

8 elements

INSTALLATION AND MAINTENANCE

NUMBER OF CHANNEL ENTRIES

2

EXTINGUISHING (ºC)

+850 ºC / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Using screws

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

Specially designed for installation in concrete floors

SCREWS REQUIRED FOR SLAB FIXING

Minimum 2 (1 per side, diagonally). It is recommended to fix the bowl with 6 screws for complete fixation.

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053090589

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
1.4

PRODUCT NET WEIGHT
1.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053090589

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
55

PACKAGING WIDTH
385

PACKAGING LENGTH
420

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.089

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
1.405

PACKAGING NET WEIGHT
1.4

PACKAGING WEIGHT UNIT
KGM