

## Customisable set with cover 2 openings and fins, 6 schuko socket outlets and 2 empty elements black S400 Indesk Duo

REF. 47403000-138



## BASIC INFORMATION

### DESCRIPTION

A profile in anodised aluminium, an enclosure painted steel, covers and fastenings manufactured in self-extinguishing halogen-free thermoplastic that guarantees no flame spread in case of fire, is what differentiates the series Simon 400 Indesk Duo from other brands. The quality of these materials is reflected in this kit to be flush mounted in the table with cover for 2 opening and fin shape, it has 6 SCHUKOS and 2 empty elements made of metal and finishes in black. A product stylish and functional that has a manual elevation system that allows to incorporate into everyday seamlessly into any space, a piece for 4 elements with a current of 16 A and a voltage of 250 volts. For connection has a connector figure Wieland ® gst18i 3 poles male in-line with patch cord of 22 cm, we must be kept in mind to complete your installation, we need to combine it with the Simon 400 Indesk Duo.

### FINISH

Black

### MATERIAL

Metal

### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

### NUMBER OF POSSIBLE ELEMENTS

2

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

### TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9005

### NUMBER OF REAR ENTRANCES

2

### RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

### NUMBER OF SOCKETS

6 sockets for standard current circuit

### VERSION

8 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS

With metal fin

### CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS

2

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION TYPE

Suitable for recessed mount in furniture.

### OPENING ORIENTATION

At 45° and 135°

### REMOVAL OF THE PLATE

Only with tool

### SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2011/65/UE RoHS; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053197370

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.45

### PRODUCT NET WEIGHT

2.45

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053197370

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

370

### PACKAGING WIDTH

135

### PACKAGING LENGTH

200

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

9990000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.45

### PACKAGING WEIGHT UNIT

KGM