

Angled voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP graphite Simon 500 Cima

REF. 50003086-038



BASIC INFORMATION

DESCRIPTION

Model of voice and data plate Number of the 50003086-038 professional range of components of components and products Simon 500 Cima, version of angled plate with dust cover with 1 element. Designed for two RJ45 connectors Category FTP with snap-fit Keystone I, II, ATT ® / Avaya ® includes clips for fastening in vertical enclosures and Horizontal without the need for an adaptor. Colour and finishes in graphite colour, Integrated components of character self-extinguishing thermoplastic and halogen-free That guarantees no flame propagation in case of fire and the Low toxicity in case of smoke Plate with dimensions of 50 x 50 x 55,4 mm and depth 55,4 mm, with features Of great versatility and adaptability to the main systems for work and Professional environments.

FINISH

Graphite

PACKAGING CONTENTS

Angled voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Angled

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RAL

7021

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

RJ45 ADAPTOR MODULE

Included in voice and data plate

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

VERSION

Single

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

54

UNITARY PACKAGING GROSS WEIGHT

0.114

PACKAGING LENGTH

215

UNITARY PACKAGING WIDTH

52

PRODUCT NET WEIGHT

0.114

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING LENGTH

215

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.052

UNITARY PACKAGING MEASUREMENT UNIT

MMT

PACKAGING EAN

8421053097656

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

603720

UNITS CONTAINED PACKAGING

20

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING HEIGHT

54

PACKAGING NET WEIGHT

2.28

PACKAGING WIDTH

52

PACKAGING WEIGHT UNIT

KGM

