

PD-8 PIR+LUX recessed On/Off white IP20

REF. 89212112-130



BASIC INFORMATION

DESCRIPTION

PIR flush-mounted presence and luminosity detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360 °. The tangential detection range is 8 m and the radial detection range is 4.5 m.

The luminosity regulation range is 2 - 1000 lux and the timing range is 5 s - 60 min. The detector configuration is done via potentiometers and remote control.

It has a TEACH operating mode. Interconnection possibility between master/master sensors for up to 10 detectors. The control output is On/Off and the maximum switchable power is 2000 W (500 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, IP 20 protection grade, and dimensions: Ø 109 x 107 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

CONTROL

On/Off

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342275

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.353

PRODUCT NET WEIGHT

0.208

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342275

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

141

PACKAGING WIDTH

141

PACKAGING LENGTH

141

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2803221

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.353

PACKAGING NET WEIGHT

0.208

PACKAGING WEIGHT UNIT

KGM