

Complete set with 5 schuko socket outlets white S400 Top

REF. 42505000-130



BASIC INFORMATION

DESCRIPTION

Adapting to the needs of innovation and functionality of the work spaces, Simon 400 Top offers the kit with 5 Schuko socket outlets and finishes in white, with a design of simple and discreet, this kit is the ideal solution to optimise the space in tables and desks at the same time as maximize the functions. With a compact dimension of 250 x 120 x 80 mm, it is designed for flush installation in furniture, quick and easy as it does not require the use of additional tools. Its quick connection Wieland and its assembly from the top of the table, facilitate and reduce the installation time. Compatible with power supplies with a voltage of 250 Volts, and 16 Ampere current, has a insulation resistance > 5 M Ω at 500 V and dielectric strength of 2000 V at 50H per minute. Functionality and innovation that adapt to the new concept of Workplace.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9016

NUMBER OF SOCKETS

5 sockets for standard current circuit

VERSION

5 elements

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195925

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.99

PRODUCT NET WEIGHT

0.99

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053195925

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

300

PACKAGING WIDTH

125

PACKAGING LENGTH

95

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3562500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

0.99

PACKAGING WEIGHT UNIT

KGM