

Aluminium bracket Ofiblock Compact for 2 elements white Simon K45

REF. KFC102/9



BASIC INFORMATION

DESCRIPTION

The greatest versatility of installation to adapt to the specific needs of each space, is the guarantee of the maximum efficiency in connectivity within the Ofiblock Compact aluminium profile of the Simon K45 collection designed for 2 elements and with finishes in a white tones tone, this ofiblock adapts to all types of space, providing a stylish minimalist style with notes. Its compact design allows a greater convergence of energy, voice, data and multimedia solutions at a lesser depth, thanks to its size of 54 x 135 x 54 mm, it also within its compact dimension, the product includes 1 blind plate to offer greater comfort in the internal distribution of cabling. Suitable for installation on walls, furniture, raised floor, surface-mounted metal with magnet, or on a DIN rail, is made of anodised aluminium and covers in self-extinguishing thermoplastic and halogen-free to protect the room in case of fire.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Simon K45 range functions and possible to combine with the Simon Electrical Wiring range.

PACKAGING CONTENTS

Ofiblock Compact aluminium profile, 1 ground connection, 1 blind plate, 1 side cover with direct cable entry, cabling gland, 1 blind side cover, screws and installation manual.

REMARKS

More compact profile to allow convergence of energy, voice, data and multimedia solutions at a lesser depth.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

KIT AVAILABILITY

No

RAL

9003

AVAILABLE IN

Available in 2, 3, 4, 5, 6, 7, 8, 9 and 10 element versions

LINKABLE

No

NUMBER OF SIDE ENTRANCES

Up to 2 cables for each side of the profile through the ACFC02/24 cover. On request, the side cover can be supplied machined according to the customer's requirements.

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SPACE FOR CABLING DISTRIBUTION

The bracket is supplied with 1 blind plate for easier internal wiring distribution.

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

NUMBER OF MODULES

2 modules

VERSION

2 elements

IP RATING

IP4X

INSTALLATION AND MAINTENANCE

CABLING ACCESS

Through the housings located at the sides of the profile.. Entry for fast-connection connectors, electrical cabling hose, voice, data and multimedia cabling through specific plates.

TYPE OF FASTENING

By fastening the bracket chosen and subsequent linking through the rear DIN rail on the profile.

SCREWS REQUIRED FOR SLAB FIXING

2 (1 per side) in combination with reference KSF4 (support not supplied with profile)

REMOVAL OF COMPONENTS

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

SECURING POSSIBILITIES

Its design allows it to be mounted on the wall, on table-top furniture, under a desk, on a raised floor, on a metal surface with a magnet, or on a DIN rail using specific fastening accessories.

REMOVAL OF COVER

Only with tool

INSTALLATION TYPE

Suitable for installation on walls, furniture, raised floors, metal surfaces with a magnet or DIN rails.

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436038912

PRODUCT NET WEIGHT

0.175

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

603900

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436038912

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.175

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

60

PACKAGING NET WEIGHT

0.175

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

183

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.175

PACKAGING LENGTH

55