2RCA connector female with trim plate aluminium Simon K45

REF. **K101B/8**



BASIC INFORMATION

DESCRIPTION

2 female RCA, of the series Simon K45, with trim plate in aluminium finish. With measures 22.5 x 45 mm, very little requires maintenance. These connectors have a screw terminal connection and it is recommended to use a maximum cabling length of 30 meters. The installation of this connector Simon K45 is very versatile, since it is possible to recess it or to install it on surface-mounted. It is the individual version of a single module, manufactured using metal components isolated thermoplastically, to avoid the hazards of fire. Also, do not carried any type of halogens. The maximum temperature that support these connectors varies in an interval of -25 to + 50 degrees centigrade. To them you simply have to use a dry and soft, clean free of corrosive products. The connectors Simon K45 they bet for the security and the ease of installation, allowing the user options varied for this purpose.

FINISH

Aluminium

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-033)

PACKAGING CONTENTS

2 female RCA, wire cable tie and instruction sheet

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
RCA

NUMBER OF CONTACTS
6

NUMBER OF POSSIBLE ELEMENTS
1/2 element

FORMAT
RCA

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
6

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-033)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436064652

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.022

PRODUCT NET WEIGHT
0.022

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436064652

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
50

PACKAGING WIDTH
42

PACKAGING LENGTH
50

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.012

PACKAGING VOLUME UNIT
HLT

PACKAGING GROSS WEIGHT
0.022

PACKAGING NET WEIGHT
0.022

PACKAGING WEIGHT UNIT
KGM