


Aluminum trunking of 2m 185x55mm with 3 compartments for K45 functions

REF. TK11143/8



BASIC INFORMATION

DESCRIPTION

Aluminum channel 2m in length and a cross-section of 160x55mm, with 3 front compartments capable of mounting all functions of the K45 range without the need for accessories, achieving significant time savings in assembly. Regardless of the designed structure, it ensures the electrical wiring is isolated from voice, data, and multimedia, as well as maintaining its correct bending radius throughout the distribution. It adapts to different architectures through its installation accessories, with the possibility of branching to Mini-channel and Cable guide via the pre-punched line. Made from high-quality anodized aluminum, it has a protection rating of IP4X and IK07. We are talking about a fireproof, self-extinguishing, and flame-retardant material. The indicated price is per meter and is supplied in lots of 3 units (6 meters in total)

FINISH

Aluminium

COMPATIBILITY

Functions K45

MATERIAL

Aluminium

ETIM CLASS

EC001938

TECHNICAL INFORMATION

IK CLASSIFICATION

09

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

REMOVAL OF COVER

No tools needed

REMOVAL OF THE FRAME

Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053264232

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0

PRODUCT NET WEIGHT

3.053

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436043398

UNITS CONTAINED PACKAGING

6

PACKAGING HEIGHT

210

PACKAGING WIDTH

132

PACKAGING LENGTH

2020

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

55994400

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

18.318

PACKAGING WEIGHT UNIT

KGM