

Flat voice and data plate with dust cover for 1 element with 2 RJ45 category 6 FTP aluminium Simon 500 Cima

REF. 50003089-033



BASIC INFORMATION

DESCRIPTION

With the plate of voice and data flat plate with finishes in Aluminium of the collection Simon 500 Cima with dust cover with 1 element and 2 RJ45 category 6 FTP, guarantees the speed in the transmission of data on any work area. Manufactured with thermoplastic materials isolated with self-extinguishing halogen-free, prevents the flame spread and toxicity by smoke in case of fire. Also, it is designed for installation in vertical and horizontal enclosures with snap-fit for fastening without using adapters. The versatility and simplicity of installation, along with its finishes in Aluminium, enhances its appearance and functionality at the same time that promotes the integration in a reduced space. Compatible with ports Keystone I, II and cabling 22-26 AWG, the flat base plate Simon 500 Cima, includes module and RJ45 connector to offer the highest and faster workplace solutions in any environment.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover, 2 RJ45 category 6 FTP and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

DUST PROTECTION

Yes

PLATE TYPE

Flat

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

FORMAT

RJ45

RJ45 ADAPTOR MODULE

Included in voice and data plate

RJ45 CONNECTION

Without insertion tool

IP RATING

IP20

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

CONNECTOR CHARACTERISTICS

category 6 FTP

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

NUMBER OF CONNECTORS

2

VERSION

Single

RJ45 CONNECTORS

Included in voice and data plate

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

NUMBER OF MODULES

1

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
170

UNITARY PACKAGING WIDTH
195

UNITARY PACKAGING LENGTH
270

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
8950500

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.057

PRODUCT NET WEIGHT
0.057

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053097915

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
223

PACKAGING WIDTH
334

PACKAGING LENGTH
425

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
0.052

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
1.14

PACKAGING WEIGHT UNIT
KGM

