

Complete kit with dual opening cover, metal fins, 4 schuko socket outlets, 4 UPS socket outlets and plate for 8 RJ45 connectors white S400 Indesk Duo

REF. 47602240-130



BASIC INFORMATION

DESCRIPTION

The 400 series stands out for the high quality of its flush-mounted pieces in furniture. This is a complete kit integrated into the table with a double opening cover, fins with 4 white schuko socket bases, 4 schuko socket bases for UPS, and plates for 8 RJ45 connectors. This product for 6 elements is made of metal and features an elegant white finish. It has 4 bases for standard current circuit of 250 volts, 4 bases for UPS, and 16 amperes of intensity. A very easy-to-use kit thanks to its manual lift system. It has a Wieland® g8t18i 3-pole male aerial connector with a 22 cm patch cord and an insulation resistance of >5 MO at 500 V. Its anodized aluminum profile combined with the painted steel enclosure makes this kit a durable and shock-resistant product.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5 MΩ a 500 V

RAL

9016

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

CURRENT (A)

16 A

RECESS DIMENSION (MM)

318 x 175 mm (± 2mm)

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with metal fin

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

8

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

SNAP-FIT TYPE

Keystone I, II and Systimax

FORMAT

Schuko

NOMINAL VOLTAGE (V~)

250 V~

NUMBER OF SOCKETS

4 sockets for standard current circuit and 4 sockets for stable current circuit (UPS)

TYPE OF POWER SUPPLY CONNECTOR

Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

NUMBER OF UPS SOCKET OUTLETS

4

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

VERSION

12 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With metal fin

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053208632

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053208632

PACKAGING VOLUME

9990000

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

370

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

135

PACKAGING NET WEIGHT

3.5

UNITARY PACKAGING GROSS
WEIGHT

3.5

PACKAGING LENGTH

200

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

3.5