


Flush-mount trim cover square shallow floor box for 8 elements grey Simon 500 Cima

REF. 52053204-035



BASIC INFORMATION

DESCRIPTION

The Trim cover for flush mounting in floor box shallow square for eight elements in grey colour of the Simon 500 Cima series is the best example of how it is possible to obtain accessories with the maximum security and the highest quality. Its innovative design has made it one of the most demanded elements. It has dimensions of 277 x 209 x 5 mm. Its installation? Is carried out without the need for tools in concrete floor and raised floor through the floor box for shallow. Its structure? Has been made with halogen-free thermoplastic material; guarantees no flame propagation in case of fire and the low toxicity in case of smoke. Also, this cover includes an optional element to combine with the floor box if not installing the same floor lining.

FINISH

Grey

PACKAGING CONTENTS

Trim cover

MATERIAL

Plastic

ETIM CLASS

EC002417

REMARKS

Optional element. To combine with the floor box if not installing the same floor finish.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IK CLASSIFICATION

08

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

AVAILABLE IN

4, 6 and 8 elements

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

NUMBER OF MODULES

8 modules

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP4X

RAL

7011

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

KIT AVAILABILITY

No

VERSION

8 elements

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION TYPE

In raised or concrete floor with shallow floor boxes

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

INSTALLATION DIRECTION

Horizontal, Vertical

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 60670-23:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053101698

PRODUCT NET WEIGHT

0.22

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

441000

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053101698

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

5

PACKAGING NET WEIGHT

0.22

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

245

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.22

PACKAGING LENGTH

360