

# USB charger x1 2.1A 5V DC type A female Simon 100

REF. 10000380-039



## BASIC INFORMATION

### DESCRIPTION

The Internet of Things or ♦Internet of Things♦ touches the world of electrical mechanisms in this series, the Simon 100 collection, a collection that revolutionizes, by giving an additional aspect, the concept of electrical mechanisms. To simplify people, to save them time, it has always been an objective priority for Simon. This series is another example. It belongs to this Simon 100 female type A 1xUSB 2.0 5 V / DC charger. This Simon 100 collection reproduces the nature of a switch and everything around you, seeking increased approach and closeness. Not having the comfort that it means having these mechanisms. In addition, Simon 100 gives you everything you need to create the most functional spaces in your home or workplace, which means higher quality of life.

### COMPATIBILITY

Frames Simon 100

### PACKAGING CONTENTS

Mechanism and instructions

### ETIM CLASS

EC002949

## TECHNICAL INFORMATION

|                                                   |                                                  |                                                  |
|---------------------------------------------------|--------------------------------------------------|--------------------------------------------------|
| AVAILABLE MARKET<br>CE                            | INDICATOR FUNCTION<br>No                         | STORAGE TEMPERATURE RANGE<br>(°C)<br>-25 - 75 °C |
| CABLE SECTION ADMITTED (MM)<br>From 1,5 to 2,5 mm | CURRENT (A)                                      | USB CHARACTERISTICS<br>10W                       |
| CONNECTOR TYPE<br>USB A                           | IP RATING<br>IP20                                | USB CURRENT (A)<br>2,1 A                         |
| NUMBER OF POSSIBLE<br>ELEMENTS<br>Half element    | TYPE OF MECHANISM<br>Insertion                   | USB VOLTAGE (V~)<br>5 Vdc                        |
| FORMAT<br>USB                                     | OPERATING TEMPERATURE<br>RANGE (°C)<br>0 - 40 °C | VERSION<br>Unique                                |
|                                                   | POWER SUPPLY (V~)<br>230 V~                      |                                                  |

## INSTALLATION AND MAINTENANCE

|                                        |                                                         |                                                      |
|----------------------------------------|---------------------------------------------------------|------------------------------------------------------|
| CABLE STRIPPING NECESSARY<br>(MM)<br>6 | INSTALLABLE IN FLUSH MOUNT<br>JUNCTION BOX<br>universal | TYPE OF TERMINAL<br>CONNECTION - FUNCTION 1<br>Screw |
| CLAW                                   | INSTALLATION TYPE<br>Suitable for flush mounting        |                                                      |

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) | EN 62368-1:2014 + A11:2017 | EN 50563:2011 + A1:2013 | EN IEC 63000:2018 ETSI | EN 301489-34 V2.1.1

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053147801

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.046

### PRODUCT NET WEIGHT

0.046

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053147801

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

55

### PACKAGING WIDTH

40

### PACKAGING LENGTH

65

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

143000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.046

### PACKAGING NET WEIGHT

0.046

### PACKAGING WEIGHT UNIT

KGM

