

## Metal mini tower with 2 heights and 2 sides for 4 elements per side stainless steel Simon 500 Cima

REF. 52510222-036



## BASIC INFORMATION

### DESCRIPTION

This product belongs to the Simon 500 Cima range. This is a metal mini-tower 2 heights and 2 sides for 4 elements for each one of the sides. Its measures are 172,5 x 221 millimetres and 133 millimetres of depth. Its installation is very simple and the product is very versatile, as it is suitable for all types of floor, whether concrete or raised. The centre frames include linkable parts that form blocks, allowing separation of the electrical part from the voice and data part for easier maintenance. Its metallic finish makes it a very innovative product that lends great modernity to any room in the home, office or premises where it is. The material used to manufacture the mini-tower is the high quality stainless steel, a material that gives a lot of resistance to the product and an extra hardness, allowing it to work in optimum even low temperatures very low and high.

### FINISH

Metal

### MATERIAL

Stainless steel

### COMPATIBILITY

Simon 500 Cima and Simon 27  
Play/Simon K45 mechanisms  
(using an adaptor)

### PACKAGING CONTENTS

Mini tower, metal partition wall,  
ground connection cable, screws  
and installation manual

### ETIM CLASS

EC001941

### REMARKS

The frame holders include linkable parts that form blocks, allowing the electrical part to be separated from the voice and data part for ease of maintenance

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

### AVAILABLE IN

1 and 2 sides

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Secured by installing the metal partition wall in the housings fitted into the box for this purpose.

### IK CLASSIFICATION

08

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 120° C

### NUMBER OF MODULES

4 per side

### VERSION

2 sides

## INSTALLATION AND MAINTENANCE

### REMOVAL OF COMPONENTS

Only with tool

### TYPE OF FASTENING

Using the screws supplied

### REMOVAL OF THE FRAME

Only with tool

### INSTALLATION DIRECTION

Vertical

### INSTALLATION TYPE

Suitable for installing in any floor type, raised or concrete

### SCREWS REQUIRED FOR FLOOR FIXING

4

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

## LOGISTICS INFORMATION

UNITARY EAN CODE

8421053099292

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053099292

PACKAGING VOLUME

5.123

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

134

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

221

PACKAGING NET WEIGHT

2.27

UNITARY PACKAGING GROSS  
WEIGHT

2.27

PACKAGING LENGTH

173

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

2.27

